


HC HOLLOWCONE



ЛТРОН ЕООД
 гр. Велико Търново
 местност Дълга Лъка
 ул. Трета 5
 тел. 062/ 601 359
 моб. 0884/ 614 800

www.tron.bg



| Code | Angle | bar | drop | l/min | l/da | | | | | | | | |
|------------------------|-------|-----|------|-------|------|------|------|------|------|------|------|------|------|
| | | | | | 4 | 6 | 8 | 10 | 12 | 14 | 16 | 18 | 20 |
| | | | | | km/h | | | | | | | | |
| HC01 ОРАНЖЕВ | 85° | 1 | F | 0.23 | 6.9 | 4.6 | 3.5 | 2.8 | 2.3 | 2.0 | 1.7 | 1.5 | 1.4 |
| | | 2 | VF | 0.33 | 9.8 | 6.5 | 4.9 | 3.9 | 3.3 | 2.8 | 2.4 | 2.2 | 2.0 |
| | | 3 | VF | 0.40 | 12.0 | 8.0 | 6.0 | 4.8 | 4.0 | 3.4 | 3.0 | 2.7 | 2.4 |
| | | 5 | VF | 0.52 | 15.5 | 10.3 | 7.7 | 6.2 | 5.2 | 4.4 | 3.9 | 3.4 | 3.1 |
| | | 8 | VF | 0.65 | 19.6 | 13.1 | 9.8 | 7.8 | 6.5 | 5.6 | 4.9 | 4.4 | 3.9 |
| | | 10 | VF | 0.73 | 21.9 | 14.6 | 11.0 | 8.8 | 7.3 | 6.3 | 5.5 | 4.9 | 4.4 |
| HC015 ЗЕЛЕН | 85° | 1 | F | 0.35 | 10.4 | 6.9 | 5.2 | 4.2 | 3.5 | 3.0 | 2.6 | 2.3 | 2.1 |
| | | 2 | F | 0.49 | 14.7 | 9.8 | 7.3 | 5.9 | 4.9 | 4.2 | 3.7 | 3.3 | 2.9 |
| | | 3 | VF | 0.60 | 18.0 | 12.0 | 9.0 | 7.2 | 6.0 | 5.1 | 4.5 | 4.0 | 3.6 |
| | | 5 | VF | 0.77 | 23.8 | 15.5 | 11.6 | 9.2 | 7.7 | 6.7 | 5.8 | 5.1 | 4.5 |
| | | 8 | VF | 0.98 | 29.4 | 19.6 | 14.7 | 11.8 | 9.8 | 8.4 | 7.3 | 6.5 | 5.9 |
| | | 10 | VF | 1.10 | 32.9 | 21.9 | 16.4 | 13.1 | 11.0 | 9.4 | 8.2 | 7.3 | 6.6 |
| HC02 ЖЪЛТ | 80° | 1 | F | 0.46 | 13.9 | 9.2 | 6.9 | 5.5 | 4.6 | 4.0 | 3.5 | 3.1 | 2.8 |
| | | 2 | F | 0.65 | 19.6 | 13.1 | 9.8 | 7.8 | 6.5 | 5.6 | 4.9 | 4.4 | 3.9 |
| | | 3 | VF | 0.80 | 24.0 | 16.0 | 12.0 | 9.6 | 8.0 | 6.9 | 6.0 | 5.3 | 4.8 |
| | | 5 | VF | 1.03 | 31.8 | 20.6 | 15.5 | 12.4 | 10.3 | 8.8 | 7.7 | 6.7 | 6.2 |
| | | 8 | VF | 1.31 | 39.2 | 26.1 | 19.6 | 15.7 | 13.1 | 11.2 | 9.8 | 8.7 | 7.8 |
| | | 10 | VF | 1.46 | 43.8 | 29.9 | 21.9 | 17.5 | 14.6 | 12.5 | 11.0 | 9.7 | 8.8 |
| HC03 СИН | 80° | 1 | F | 0.69 | 20.8 | 13.9 | 10.4 | 8.3 | 6.9 | 5.9 | 5.2 | 4.6 | 4.2 |
| | | 2 | F | 0.98 | 29.4 | 19.6 | 14.7 | 11.8 | 9.8 | 8.4 | 7.3 | 6.5 | 5.9 |
| | | 3 | VF | 1.20 | 36.0 | 24.0 | 18.0 | 14.4 | 12.0 | 10.3 | 9.0 | 8.0 | 7.2 |
| | | 5 | VF | 1.55 | 46.5 | 31.0 | 23.2 | 18.6 | 15.5 | 13.3 | 11.6 | 10.3 | 9.3 |
| | | 8 | VF | 1.96 | 58.8 | 39.2 | 29.4 | 23.5 | 19.6 | 16.8 | 14.7 | 13.1 | 11.8 |
| | | 10 | VF | 2.19 | 65.7 | 43.8 | 32.9 | 26.3 | 21.9 | 18.8 | 16.4 | 14.6 | 13.1 |
| HC035 БОРДО | 80° | 1 | F | 0.81 | 24.2 | 16.2 | 12.1 | 9.7 | 8.1 | 6.9 | 6.1 | 5.4 | 4.8 |
| | | 2 | F | 1.14 | 34.3 | 22.9 | 17.1 | 13.7 | 11.4 | 9.8 | 8.6 | 7.6 | 6.9 |
| | | 3 | VF | 1.40 | 42.0 | 28.0 | 21.0 | 16.8 | 14.0 | 12.0 | 10.2 | 9.3 | 8.4 |
| | | 5 | VF | 1.81 | 55.9 | 36.2 | 27.2 | 21.7 | 18.1 | 15.7 | 13.6 | 11.9 | 10.7 |
| | | 8 | VF | 2.29 | 68.6 | 45.7 | 34.3 | 27.4 | 22.9 | 19.6 | 17.1 | 15.2 | 13.7 |
| | | 10 | VF | 2.56 | 76.7 | 51.1 | 38.3 | 30.7 | 25.6 | 21.9 | 19.2 | 17.0 | 15.3 |
| HC04 ЧЕРВЕН | 80° | 1 | F | 0.92 | 27.7 | 18.5 | 13.9 | 11.1 | 9.2 | 7.9 | 6.9 | 6.2 | 5.5 |
| | | 2 | F | 1.31 | 39.2 | 26.1 | 19.6 | 15.7 | 13.1 | 11.2 | 9.8 | 8.7 | 7.8 |
| | | 3 | VF | 1.60 | 48.0 | 32.0 | 24.0 | 19.2 | 16.0 | 13.7 | 12.0 | 10.7 | 9.6 |
| | | 5 | VF | 2.07 | 62.0 | 41.3 | 31.0 | 24.8 | 20.7 | 17.7 | 15.5 | 13.8 | 12.4 |
| | | 8 | VF | 2.61 | 78.4 | 52.3 | 39.2 | 31.4 | 26.1 | 22.4 | 19.6 | 17.4 | 15.7 |
| | | 10 | VF | 2.92 | 87.6 | 58.4 | 43.8 | 35.1 | 29.2 | 25.0 | 21.9 | 19.5 | 17.5 |

| DROP SIZE RATING | |
|---------------------|---------------|
| VF Very fine | < 136µm |
| F Fine | 136µm ÷ 177µm |
| M Medium | 177µm ÷ 218µm |

µm = thousandth of millimeter (E.g.: 250µm = 0.25 mm)