

AFC FAN AIR CERAMIC





1.5÷8 bar
WORK
Working pressure

110°
Spraying angle

402900xx
Cap

Ceramic
Material



ЕЛТРОН ЕООД
гр. Велико Търново
местност Дълга Лъка
ул. Трета 5
тел. 062/ 601 359
моб. 0884/ 614 800
www.tron.bg
www.eltron-bg.com

Code	bar	Drop Size Rating	I/min	l/da									
				4	6	8	10	12	14	16	18	20	25
km/h													
AFC 11001 оранж	1.5	XC	0.28	8.5	5.7	4.2	3.4	2.8	2.4	2.1	1.9	1.7	1.4
	3	XC	0.40	12.0	8.0	6.0	4.8	4.0	3.4	3.0	2.7	2.4	1.9
	4	C	0.46	13.9	9.2	6.9	5.5	4.6	4.0	3.5	3.1	2.8	2.2
	6	C	0.57	17.0	11.3	8.5	6.8	5.7	4.8	4.2	3.8	3.4	2.7
	8	C	0.65	19.6	13.1	9.8	7.8	6.5	5.6	4.9	4.4	3.9	3.1
AFC 110015 зелен	1.5	XC	0.42	12.7	8.5	6.4	5.1	4.2	3.6	3.2	2.8	2.5	2.0
	3	VC	0.60	18.0	12.0	9.0	7.2	6.0	5.1	4.5	4.0	3.6	2.9
	4	C	0.69	20.8	13.9	10.4	8.3	6.9	5.9	5.2	4.6	4.2	3.3
	6	C	0.85	25.5	17.0	12.7	10.2	8.5	7.3	6.4	5.7	5.1	4.1
	8	C	0.98	29.4	19.6	14.7	11.8	9.8	8.4	7.3	6.5	5.9	4.7
AFC 11002 жълт	1.5	UC	0.57	17.0	11.3	8.5	6.8	5.7	4.8	4.2	3.8	3.4	2.7
	3	XC	0.80	24.0	16.0	12.0	9.6	8.0	6.9	6.0	5.3	4.8	3.8
	4	VC	0.92	27.7	18.5	13.9	11.1	9.2	7.9	6.9	6.2	5.5	4.4
	6	C	1.13	33.9	22.6	17.0	13.6	11.3	9.7	8.5	7.5	6.8	5.4
	8	C	1.31	39.2	26.1	19.6	15.7	13.1	11.2	9.8	8.7	7.8	6.3
AFC 110025 лилав	1.5	XC	0.71	21.2	14.1	10.6	8.5	7.1	6.1	5.3	4.7	4.2	3.4
	3	VC	1.00	30.0	20.0	15.0	12.0	10.0	8.6	7.5	6.7	6.0	4.8
	4	C	1.15	34.6	23.1	17.3	13.9	11.5	9.9	8.7	7.7	6.9	5.5
	6	C	1.41	42.4	28.3	21.2	17.0	14.1	12.1	10.6	9.4	8.5	6.8
	8	C	1.63	49.0	32.7	24.5	19.6	16.3	14.0	12.2	10.9	9.8	7.8
AFC 11003 син	1.5	XC	0.85	25.5	17.0	12.7	10.2	8.5	7.3	6.4	5.7	5.1	4.1
	3	VC	1.20	36.0	24.0	18.0	14.4	12.0	10.3	9.0	8.0	7.2	5.8
	4	VC	1.39	41.6	27.7	20.8	16.6	13.9	11.9	10.4	9.2	8.3	6.7
	6	C	1.70	50.9	33.9	25.5	20.4	17.0	14.5	12.7	11.3	10.2	8.1
	8	C	1.96	58.8	39.2	29.4	23.5	19.6	16.8	14.7	13.1	11.8	9.4
AFC 11004 червен	1.5	XC	1.13	33.9	22.6	17.0	13.6	11.3	9.7	8.5	7.5	6.8	5.4
	3	XC	1.60	48.0	32.0	24.0	19.2	16.0	13.7	12.0	10.7	9.6	7.7
	4	VC	1.85	55.4	37.0	27.7	22.2	18.5	15.8	13.9	12.3	11.1	8.9
	6	C	2.26	67.9	45.3	33.9	27.2	22.6	19.4	17.0	15.1	13.6	10.9
	8	C	2.61	78.4	52.3	39.2	31.4	26.1	22.4	19.6	17.4	15.7	12.5
AFC 11005 кафяв	1.5	UC	1.41	42.4	28.3	21.2	17.0	14.1	12.1	10.6	9.4	8.5	6.8
	3	XC	2.00	60.0	40.0	30.0	24.0	20.0	17.1	15.0	13.3	12.0	9.6
	4	VC	2.31	69.3	46.2	34.6	27.7	23.1	19.8	17.3	15.4	13.9	11.1
	6	VC	2.83	84.9	56.6	42.4	33.9	28.3	24.2	21.2	18.9	17.0	13.6
	8	C	3.27	98.0	65.3	49.0	39.2	32.7	28.0	24.5	21.8	19.6	15.7
AFC 11006 сив	1.5	UC	1.70	50.9	33.9	25.5	20.4	17.0	14.5	12.7	11.3	10.2	8.1
	3	XC	2.40	72.0	48.0	36.0	28.8	24.0	20.6	18.0	16.0	14.4	11.5
	4	XC	2.77	83.1	55.4	41.6	33.3	27.7	23.8	20.8	18.5	16.6	13.3
	6	VC	3.39	101.8	67.9	50.9	40.7	33.9	29.1	25.5	22.6	20.4	16.3
	8	C	3.92	117.6	78.4	58.8	47.0	39.2	33.6	29.4	26.1	23.5	18.8

DROP SIZE RATING	
C Coarse	218µm ÷ 349µm
VC Very coarse	349µm ÷ 428µm
XC Extremely coarse	428µm ÷ 622µm
UC Ultra coarse	> 622 µm

µm = thousandth of millimeter (E.g.: 250µm = 0.25 mm)